

SIER ELECTRONICS CO., LTD

A: No.1 Binhe Nan Road, Baoji 721004, Shaanxi, P.R.China

Tel: +86 917 3652001

Fax: +86 917 3652001

Email: kenny@sierselectro.com

Web: www.sierselectro.com

SVS03 Vibration Sensor

Features

- Reliable performance, easy application
- Short protection and reverse polarity protection
- Excellent long term stability
- Customized design available



Introduction

SVS03 Electro-Magnetic version vibration sensor, it is very easy application and have compact size. It can be widely used to monitor the working status of motors, pumps, compressors or other equipment which have move parts. Magnetic mounting and thread mounting optional.


Specification

Item	Specification
Range	0-200mm/s, 0-50g
Frequency	4.5~1000Hz
Accuracy	±0.5%FS
Thermal drift	≤0.1%/°C
Application temp.	-40~85°C
Power supply	24VDC
Output signal	4-20mA. 0-5V. RS485. etc
Protection	IP65
Electrical connection	M12 connector or cable exit

Construction Material

Housing	SS304
Cable	PVC

Outline Dimension



Order Guide

SVS03	Vibration Sensor				
	Range	0-200mm/s, 0-50g			
	[0~X] mm/s	X: the range required			
		Code	Mounting		
		01	M5*0.8 thread		
		02	M8*1.25 thread		
		03	M10*1.5 thread		
		04	Magnetic		
		05	Customized please specify		
			Code	Others	
			B2	Cable exit, please mention length	
			B3	M12 connector	
SVS03	[0~1 mm/s]	01	B2	the whole spec	